



WIP-20 (G/W)



Prime Business IP Phone

Wevetel WIP20 is more than an efficient telephone but a delicate work of art, providing a smart and smooth business communication experience for enterprises. As the prime business phone featuring 2.8 color screen and necessary VoIP features and other extended features. WIP20 is a perfect combination of elegant outside and powerful inside.



Next-Generation Communication Solutions

- ✓ 2.8-inch color screen.
- ✓ Support audio codec G.722 and Opus, HD audio on speakerphone and handset.
- ✓ Support 6-way audio conference.
- ✓ Available to link with security products, can be easily customized into various security solutions for reducing investment.
- ✓ Dual Gigabit ports, integrated PoE.
- ✓ Two installation methods of desktop stand and wall mountable.
- ✓ Up to 21 DSS keys, every DSS key can be set as Line/BLF/ Speed Dial Key.

Generic

- 6 SIP lines
- HD voice
- PoE enabled
- Intelligent DSS keys
- 2.8-inch (320x240)color screen
- Handset / hands-free / headset mode
- Desktop Stand / Wall-mounted (optional)
- Optional externalpower supply

Phone Functions

- Local Phonebook (1000 entries)
- Remote Phonebook(XML/LDAP)
- Call logs (In/Out/Missed,1000 entries)
- Blocked List/Allowed List
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Support Bluetooth headset (Via BT DongleBT20)
- I Support Wi-Fi Dongle (Via WF20)
- Support Poly wireless headset(Through Poly APD-80 EHS Cable)
- Support Jabra wireless headset (Through Wevetel EHS20 EHS Cable)

- Support Recording
- Action URL / Active URI
- XML Browser
- Customize Background
- Customize Boot Logo
- uaCSTA
- Customize Incoming Call Ringtone
- Time Plan (timed reboot/timed forward/timed upgrade/timed config)
- Hidden DTMF
- Ring From Headset
- Customize DSS icon
- Customize DSS LED lights
- Customize BLF
- Customize UI Display

Call Functions

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)/Ban Anonymous call
- Call Forward (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Predial
- Call Back
- Do-Not-Disturb(DND)/Timed DND
- Auto-Answering
- SIP SMS
- Voice Message
- 6-way Audio Conference
- Hot Line
- Hot Desking
- Direct IP call without SIP proxy
- Fuzzy Search Call
- Action Plan
- Dial Plan
- Call Completion/Auto Redial
- Primary and Backup SIP Servers
- Default Ext Line
- Multicast

Audio

- HD Voice:HD handset, HD speaker
- Wideband ADC/DAC16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726, G.729,G.729A, G.729B, G.729AB, iLBC
- Wideband Codec:G.722, Opus
- Full-duplex AcousticEcho Cancellor (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- VQM voice quality monitoring

Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Network AccessControl: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- DNS-SRV (RFC 3263)
- Support Redundant Servers
- Agent
- Hhttps Mutual Authentication
- Wi-Fi Security Mode: WPA/WPA2-PSK/802.1X EAP

Protocols

- SIP v1 (RFC2543) v2(RFC3261)
- UDP/TCP/TLS
- RTP/RTCP/SRTP (Optional/Compulsory)
- STUN
- DHCP
- IPv6
- LLDP
- PPPoE

- LLDP
- PPPoE
- 802.1x
- 802.1p/Q
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Screenshot
- Web Management Portal
- Web-based Packet Dump
- Configuration Export/ Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog
- Network Firewall
- Online Upgrade

Physical Specifications

- LCD:2.8-inch (320x240) color screen
- Keypad: 39 keys, including
 - 7 DSS keys with LED indicator light
 - 6 Function keys (Contact, Hold, MWI, Mute, Headset, Redial)
 - 4 Soft-keys
 - 4 Navigation keys
 - 1 OK key
 - 1 Return key
 - 12 Standard Phone Digits keys
 - 2 Volume Control keys, Up/Down
 - 1 Hands-free key
- HD Handset(RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5.EEthernet Cable x1
- Desk Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handsetx1, Headset x1

- RJ45 Port x2: Networkx1, PC x1 (Bridged to Network)
- USB2.0 Port x1: Standard A, Connect with Flash Driver & USB headset and USB Dongle
- Security Slot x1
- Power: DC5V / 2A or PoE
 - POE complies with the IEEE 802.3af standard
 - Power adapter:
 - Input:100-240VAC~50/60Hz
 - Output:5V/2A
- Power Consumption (Adapter): 0.816~4.36W
- Power Consumption (PoE): 1.28~6.3W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation:
 - Desktop Stand
 - Wall-mounted (optional)
- Color: Dark Grey
- Qty/CTN: 10pcs
- N.W/CTN:11.45 kg
- G.W/CTN:12.5 kg
- Device Dimensions:
 - Desktop Stand (40°): 203.85x170.76x166.7 mm
 - Desktop Stand (45°): 203.85x162.5x173.8 mm
 - Wall mountable: 203.85x91x212.5 mm
- Gift Box Dimensions: 307x258x71 mm
- Outer CTN Dimensions: 536x380x327 mm (10 PCS)



03-8230 3003



www.wevetel.com



2-1, Jln Jalil 1, Bukit Jalil, 57000 Kuala Lumpur, Federal Territory of Kuala Lumpur



Wevo System Sdn Bhd